

Safety Data Sheet



Revision Number: 003.1

Issue date: 07/12/2022

1. PRODUCT AND COMPANY IDENTIFICATION

Product name:	LOCTITE EA 9658 100NWG AERO known as HYSOL EA 9658 .100 NWG	IDH number:	870989
Product type/use:	Adhesive for the Aerospace Industry	Item number:	AT9361509
Restriction of Use:	None identified	Region:	United States
Company address:	Henkel Corporation One Henkel Way Rocky Hill, Connecticut 06067	Contact information:	Telephone: +1 (860) 571-5100 MEDICAL EMERGENCY Phone: Poison Control Center 1-877-671-4608 (toll free) or 1-303-592-1711 TRANSPORT EMERGENCY Phone: CHEMTREC 1-800-424-9300 (toll free) or 1-703-527-3887 Internet: www.henkelna.com

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

WARNING: CAUSES SKIN IRRITATION.
MAY CAUSE AN ALLERGIC SKIN REACTION.
CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR
REPEATED EXPOSURE.

HAZARD CLASS	HAZARD CATEGORY
SKIN IRRITATION	2
EYE IRRITATION	2A
SKIN SENSITIZATION	1
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE	2

PICTOGRAM(S)



Precautionary Statements

Prevention:	Do not breathe dust or fumes. Wash affected area thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves, eye protection, and face protection.
Response:	IF ON SKIN: Wash with plenty of water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if you feel unwell. If skin irritation or rash occurs: Get medical attention. If eye irritation persists: Get medical attention. Take off contaminated clothing.
Storage:	Not prescribed
Disposal:	Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.

Classification complies with OSHA Hazard Communication Standard (29 CFR 1910.1200) and is consistent with the provisions of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Hazardous Component(s)	CAS Number	Percentage*
Aluminum	7429-90-5	30 - 60
Polyfunctional epoxy resin	Proprietary	10 - 30

IDH number: 870989

Product name: LOCTITE EA 9658 100NWG AERO known as HYSOL EA 9658 .100 NWG

Epoxy resin adduct	Proprietary	10 - 30
dapsone	80-08-0	5 - 10
Epoxy resin	Proprietary	5 - 10
Treated fumed silica	67762-90-7	1 - 5

* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

4. FIRST AID MEASURES

Inhalation:	If inhaled, immediately remove the affected person to fresh air. If symptoms develop and persist, get medical attention.
Skin contact:	Remove contaminated clothing and footwear. Immediately wash skin thoroughly with soap and water. If symptoms develop and persist, get medical attention.
Eye contact:	In case of contact with the eyes, rinse immediately with plenty of water for 15 minutes, and seek immediate medical attention.
Ingestion:	Get immediate medical attention. Do not induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions.
Symptoms:	See Section 11.
Notes to physician:	Treat symptomatically and supportively.

5. FIRE FIGHTING MEASURES

Extinguishing media:	Water spray (fog), foam, dry chemical or carbon dioxide.
Special firefighting procedures:	Wear full protective clothing. Wear self-contained breathing apparatus.
Unusual fire or explosion hazards:	May liberate large quantities of dense, foul-smelling smoke which may contain unidentified toxic gasses.
Hazardous combustion products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons.

6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

Environmental precautions:	Prevent further leakage or spillage if safe to do so. Wear appropriate protective equipment and clothing during clean-up. Do not allow product to enter sewer or waterways.
Clean-up methods:	Scrape up spilled material and place in a closed container for disposal. Dispose of according to Federal, State and local governmental regulations.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not breathe fumes or dust from this material. Use only with adequate ventilation. For industrial use only.
Storage:	Keep container tightly closed and in a cool, well-ventilated place away from incompatible materials.

For information on product shelf life, please review labels on container or check the Technical Data Sheet.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

Hazardous Component(s)	ACGIH TLV	OSHA PEL	AIHA WEEL	OTHER
Aluminum	1 mg/m3 TWA Respirable fraction.	15 mg/m3 PEL (as Al) Total dust. 5 mg/m3 PEL (as Al) Respirable fraction. 15 MPPCF TWA Respirable fraction. 50 MPPCF TWA Total dust. 5 mg/m3 TWA Respirable fraction. 15 mg/m3 TWA Total dust.	None	None
Polyfunctional epoxy resin	None	None	None	None
Epoxy resin adduct	None	None	None	None
dapsone	None	None	None	None
Epoxy resin	None	None	None	None
Treated fumed silica	10 mg/m3 TWA Inhalable dust. 3 mg/m3 TWA Respirable fraction.	15 mg/m3 TWA Total dust. 5 mg/m3 TWA Respirable fraction.	None	None

Engineering controls:	Ventilation should effectively remove and prevent buildup of any dust generated from the handling of this product.
Respiratory protection:	When dusts or thermal processing fumes are generated and ventilation is not sufficient to effectively remove them, appropriate NIOSH/MSHA approved respiratory protection must be provided.
Eye/face protection:	Wear safety glasses; chemical goggles (if splashing is possible).
Skin protection:	Wear impervious gloves for prolonged contact. Use of impervious apron and boots are recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Solid
Color:	grey
Odor:	Slight
Odor threshold:	Not available.
pH:	Not determined
Vapor pressure:	Nil
Boiling point/range:	Not determined
Melting point/ range:	Not determined
Specific gravity:	Not applicable
Vapor density:	Not applicable, Product is a solid.
Flash point:	Not applicable
Flammable/Explosive limits - lower:	Not determined
Flammable/Explosive limits - upper:	Not determined
Autoignition temperature:	Not determined
Flammability:	The product is not flammable.
Evaporation rate:	Not determined
Solubility in water:	Insoluble
Partition coefficient (n-octanol/water):	Not determined
VOC content:	< 1 % (calculated)
Viscosity:	Not available.
Decomposition temperature:	> 200 °C

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Hazardous reactions:	May occur.
Hazardous decomposition products:	Upon decomposition, this product emits carbon monoxide, carbon dioxide and/or low molecular weight hydrocarbons. Oxides of nitrogen.
Incompatible materials:	This product may react with strong acids or oxidizing agents.
Reactivity:	Not available.
Conditions to avoid:	Keep away from heat, ignition sources and incompatible materials.

11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes

Potential Health Effects/Symptoms

Inhalation:	Inhalation of dust generated by this material may cause respiratory tract irritation. May be harmful if inhaled.
Skin contact:	This product is irritating to the skin. This product may cause an allergic skin reaction. May be harmful if absorbed through skin.
Eye contact:	This product may be severely irritating to the eyes.
Ingestion:	Ingestion of this product may cause nausea, vomiting and diarrhea. May be harmful if swallowed.

Hazardous Component(s)	LD50s and LC50s	Immediate and Delayed Health Effects
Aluminum	Inhalation LC50 (Rat, 4 h) = > 0.888 mg/l Inhalation LC50 (Rat, 4 h) = > 2.3 mg/l	Central nervous system, Irritant, Lung
Polyfunctional epoxy resin	Inhalation LC50 (Rat, 4 h) = > 30 mg/m3	Allergen, Blood, Central nervous system, Gastrointestinal, Irritant, Kidney, Liver, Mutagen, Nervous System
Epoxy resin adduct	None	No Records
dapsone	None	Allergen, Blood, Eyes, Irritant, Kidney, Nervous System, Skin
Epoxy resin	None	Allergen, Irritant
Treated fumed silica	None	Irritant

Hazardous Component(s)	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen (Specifically Regulated)
Aluminum	No	No	No
Polyfunctional epoxy resin	No	No	No
Epoxy resin adduct	No	No	No
dapsone	No	No	No
Epoxy resin	No	No	No
Treated fumed silica	No	No	No

12. ECOLOGICAL INFORMATION

Ecological information: Not available.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose of according to Federal, State and local governmental regulations.

14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

U.S. Department of Transportation Ground (49 CFR)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

Water Transportation (IMO/IMDG)

Proper shipping name: Not regulated
Hazard class or division: None
Identification number: None
Packing group: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed as active or are exempt from listing on the Toxic Substances Control Act (TSCA) inventory.
TSCA 12 (b) Export Notification: None above reporting de minimis
CERCLA/SARA Section 302 EHS: None above reporting de minimis.
CERCLA/SARA Section 311/312: Immediate Health, Delayed Health
CERCLA/SARA Section 313: This product contains the following toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 (40 CFR 372). Aluminum (CAS# 7429-90-5).
California Proposition 65: This product contains a chemical known in the State of California to cause cancer. This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDSL Status: One or more components are not listed on, and are not exempt from listing on either the Domestic Substances List or the Non-Domestic Substances List.

16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 3,8,11,12

Prepared by: Product Safety and Regulatory Affairs

Issue date: 07/12/2022

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.

This Safety Data Sheet has been generated based on OSHA Hazard Communication Standard (29 CFR 1910.1200) and provides information in accordance with U.S. federal law only. No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.